



PİSTON KEÇELERİ / PISTON SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LK 101	PU NBR FKM	400 160 160	-30 -25 -20	110 100 220	0,5
	LK 102	PU / POM	700	-30 -25 -20	100 100 200	0,5
	LK 102R	PU / POM	700	-30	100	0,5
	LK 103	PU / NBR	400	-25	100	0,5
	LK 104	PU / NBR / POM	700	-25	100	0,5
	LK 104R	PU / NBR / POM	700	-25	100	0,5
	LK 105	NBR FKM	160 160	-25 -20	100 200	0,5
	LK 205	PU NBR FKM	25	-30 -25 -20	100 100 200	1
	LK 106	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LK 107	PU / NBR	400	-25	100	0,5
	LK 108	PU / NBR PTFE / NBR PTFE / FKM	250 400 400	-25 -25 -20	100 100 200	1 15 15
	LK 109	PU / NBR / POM		-25	100	0,5
	LK 109D	PU / NBR / POM	400	-25	100	0,5
	LK 109H	PU / NBR / POM	400	-25	100	0,5
	LK 109N	PU / NBR / POM	400	-25	100	0,5
	LK 110 - 112	PU / POM NBR / POM FKM / PTFE	500 250 250	-30 -25 -20	100 100 200	0,5
	LK 116	PU NBR FKM	160 160 160	-30 -25 -20	110 100 200	0,5

PİSTON KEÇELERİ / PISTON SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LK 216	PU NBR FKM	160 160 160	-30 -25 -20	110 100 200	0.5
	LK 117	PU / POM	250	-30	100	0.5
	LK 118	PU / NBR	400	-25	100	0.5
	LK 119	PTFE / SPRING	160	-200	260	15
	LK 120	NBR / POM FKM / PTFE	700 700	-25 -20	100 220	0.5
	LK 122	PU / NBR / POM	400	-25	100	0.5
	LK 222	PTFE / NBR / POM PTFE / FKM / PTFE	500 400	-25 -20	100 220	15
	LK 123	PU / POM	400	-30	100	0.5
	LK 123N	PU / NBR / POM	400	-25	100	0.5
	LK 123H	PU / NBR / POM	400	-25	100	0.5
	LK 123D	PU / NBR / POM	400	-25	100	0.5
	LK 124	PU NBR FKM	500 250 250	-30 -25 -20	100 100 200	0.5
	LK 125	PTFE / NBR PTFE / FKM	400 400	-25 -20	100 200	15
	LK 126	PU NBR	400 160	-30 -25	110 100	0.5
	LK 127	PU	400	-30	110	0.5
	LK 138	PTFE / NBR PTFE / FKM	400 400	-25 -20	100 200	15
	LK 238	PTFE / NBR PTFE / FKM	400	-30 -20	100 200	10



PİSTON KEÇELERİ / PISTON SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LK 139	PTFE / SPRING	160	-200	260	15
	LK 140	PU / NBR	250	-25	100	1
	LK 141	PU NBR	400 160	-30 -25	110 100	0,5
	LK 142	PTFE / NBR PTFE / FKM	350 350	-25 -20	100 200	15
	LK 144	PTFE / NBR PTFE / FKM	400	-25 -20	100 200	2
	LK 143	PU / NBR	400	-20	100	0.5
	LK 199	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LK 145	PTFE / NBR PTFE / FKM	400 400	-25 -20	100 200	15

BOĞAZ KEÇELERİ / ROD SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LS 101	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LS 102	PU / POM	700	-30 -25 -20	100 100 200	0,5
	LS 102R	PU / POM	700	-30	100	0,5
	LS 103	PU / NBR	400	-25	100	0,5
	LS 104	PU / NBR / POM	700	-25	100	0,5
	LS 104R	PU / NBR / POM	700	-25	100	0,5
	LS 105	NBR FKM	160 160	-25 -20	100 200	0,5
	LS 205	PU NBR FKM	25	-30 -25 -20	100 100 200	1

BOĞAZ KEÇELERİ / ROD SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LS 106	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LS 107	PU / NBR	400	-25	100	0,5
	LS 108	PU NBR	400 160	-30 -25	110 100	0,5
	LS 109	PU / NBR PTFE / NBR PTFE / FKM	250 400 400	-25 -25 -20	100 100 200	1 15 15
	LS 110-112	PU / POM NBR / POM FKM / POM	500 250 250	-30 -25 -20	100 100 200	0,5
	LS 116	PU NBR FKM	160 160 160	-30 -25 -20	110 100 200	0,5
	LS 216	PU NBR FKM	160 160 160	-30 -25 -20	110 100 200	0,5
	LS 117	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LS 118	PTFE / SPRING	150	-200	260	2
	LS 117R	PU / POM	700	-30	100	0,5
	LS 119	PTFE / SPRING	160	-200	260	15
	LS 120	NBR	700	-25	100	0,5
	LS 121	PU / NBR	400	-25	100	0,5
	LS 124	PU / NBR PTFE / NBR PTFE / FKM	250 400 400	-25 -25 -20	100 100 200	1 15
	LS 125	PU / NBR	400	-25	100	0,5
	LS 126 - 128	PTFE	100	-200	260	1,5
	LS 129	PU / NBR PTFE / NBR PTFE / FKM	250 400 400	-25 -25 -20	100 100 220	1 15

BOĞAZ KEÇELERİ / ROD SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LS 130	NBR	160	-25	100	0.5
	LS 131	PU NBR	400 160	-30 -25	110 100	0.5
	LS 138	PTFE / NBR	400	-25	100	15
	LS 238	PTFE / NBR	400	-25	100	15
	LS 139	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LS 141	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5
	LS 142	PTFE / NBR PTFE / FKM	350 350	-25 -20	100 200	0,5
	LS 199	PU NBR FKM	400 160 160	-30 -25 -20	110 100 200	0,5

TOZ KEÇELERİ / WIPERS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LA 101	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 102	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 103	PU / ALU NBR / ALU FKM / ALU		-30 -25 -20	110 100 200	4
	LA 104	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 105	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 106	PU / ALU NBR / ALU FKM / ALU		-30 -25 -20	110 100 200	4
	LA 107	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 108	PU NBR FKM		-30 -25 -20	110 100 200	4

TOZ KEÇELERİ / WIPERS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LA 109	PU NBR FKM		-30 -25 -20	110 100 220	4
	LA 111	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 112	PU NBR FKM		-30 -25 -20	110 100 200	4
	LA 211	PU NBR FKM		-30 -25 -20	105 100 200	4
	LA 212	PU NBR FKM		-30 -25 -20	110 100 220	4
	LA 113	PU NBR FKM		-30 -25 -20	110 100 220	4
	LA 213	PU NBR FKM		-30 -25 -20	110 100 220	4
	LA 114	PU NBR FKM		-30 -25 -20	110 100 220	4
	LA 115	PTFE / NBR PTFE / FKM		-25 -20	100 200	15
	LA 116	PTFE / NBR PTFE / FKM	16	-25 -20	100 200	15
	LA 117	PTFE / NBR PTFE / FKM	16	-25 -20	100 200	15
	LA 118	PTFE / NBR PTFE / FKM	16	-25 -20	100 200	15
	LA 119	PTFE / NBR PTFE / FKM	16	-25 -20	100 200	15

DÖNER MİL KEÇELERİ / ROTARY SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LR 101	PU / ALU NBR / ALU FKM / ALU	0.5 0.5 0.5	-30 -25 -20	110 110 220	5 10 15
	LR 102	PU / ALU NBR / ALU FKM / ALU	0.5 0.5 0.5	-30 -25 -20	110 110 220	5 10 15
	LR 103	PU / POM NBR / POM FKM / PTFE	400 250 250	-30 -25 -20	100 100 200	0,2

DÖNER MİL KEÇELERİ / ROTARY SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LR 104	PU NBR FKM	160 100 100	-30 -25 -20	110 100 200	0,2
	LR 105	PU NBR FKM	160 100 100	-30 -25 -20	110 100 200	0,2
	LR 106	NBR FKM		-25 -20	100 200	25
	LR 107	NBR FKM		-25 -20	100 200	25
	LR 108	Tüm uygun malzemeler / All possible materials	Uygulamaya göre / Upon Application	Uygulamaya göre / Upon Application		Uygulamaya göre / Upon Application
	LR 109	PU NBR FKM PTFE	600 160 160 160	-30 -25 -20 -200	110 100 200 260	
	LR 110	PU,PTFE / NBR PTFE / FKM	350	-25 -20	100 200	0.4
	LR 111	PU,PTFE / NBR PTFE / FKM	350	-25 -20	100 220	0.4
	LR 112	PU NBR	160 100	-30 -25	110 100	0.2 0,2
	LR 113	PU / ALU NBR / ALU FKM / ALU	400 250 250	-30 -25 -20	100 100 200	0,2
	LR 115	PTFE / NBR PTFE / FKM	350	-25 -20	100 200	0.4
	LR 116	PTFE / NBR PTFE / FKM	350	-25 -20	100 200	0.4
	LR 117	PTFE / SPRING	150	-200	260	2
	LR 121	PTFE / SPRING	150	-200	260	2
	LR 119	PTFE / SPRING		-200	260	5 10 15
	LR 118	PTFE / SPRING	150	-200	260	1
	LR 201	PU / ALU NBR / ALU FKM / ALU	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15

DÖNER MİL KEÇELERİ / ROTARY SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LR 202	PU / ALU NBR / ALU FKM / ALU	0,5 0,5 0,5	-30 -25 -20	110 100 220	5 10 15
	LR 203	PU / ALU NBR / ALU FKM / ALU	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15
	LR 204	PU NBR FKM	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15
	LR 205	PU NBR FKM	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15
	LR 206	PU NBR FKM	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15
	LR 207	PU NBR FKM	0,5 0,5 0,5	-30 -25 -20	110 100 200	5 10 15

STATİK SIZDIRMAZLIKLAR / STATIC SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LFL 101					
	LFL 102					
	LFL 103					
	LFL 104					
	LFL 105					
	LFL 106	PU NBR FKM	400 160 160	-30 -25 -20	110 100 220	
	LFL 107					
	LFL 108	PU	500	-30	110	0,5
	LFL 109	PU NBR FKM	400 160 160	-30 -25 -20	110 100 220	0,5
	LFL 110	PU NBR FKM	400 160 160	-30 -25 -20	110 100 220	0,5



STATİK SIZDIRMAZLIKLAR / STATIC SEALS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LFL 111	PU NBR FKM	400 160 160	-30 -25 -20	110 100 220	0,5

YASTIKLAMALAR / BACK UP RINGS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LST 108	PU POM PTFE		-30 -50 -200	110 100 260	
	LST 109	PU POM PTFE		-30 -50 -200	110 100 260	
	LST 110	PU POM PTFE		-30 -50 -200	110 100 260	
	LST 111	PU POM PTFE		-30 -50 -200	110 100 260	
	LST 112	PU POM PTFE		-30 -50 -200	110 100 260	
	LST 113	PU POM PTFE		-30 -50 -200	110 100 260	

YATAKLAMALAR / GUIDE RINGS

Profil / Profile	Tip / Type	Standart Malzeme / Standard Material	Basınç / Pressure (bar)	Çalışma Sıcaklığı / Working Temperature(°C)		Kayma Hızı (m/sn) / Sliding Speed (m/sec)
	LF 101	POM PTFE		-50 -200	100 260	4
	LF 102	POM PTFE		-50 -200	100 260	4
	LF 103	POM PTFE		-50 -200	100 260	4
	LF 104	POM PTFE		-50 -200	100 260	4
	LF 105	POM PTFE		-50 -200	100 260	4
	LF 106	POM PTFE		-50 -200	100 260	4
	LF 107	POM PTFE		-50 -200	100 260	4
	LF 108	POM PTFE		-50 -200	100 260	4
	LFB 102	POM PTFE		-50 -200	100 260	4